

ELITE 2FT LED FIXTURE

Product Code:LED2HWIRED
INSTRUCTIONS FOR USE



IMPORTANT: PLEASE READ THESE INSTRUCTIONS CAREFULLY. NOTE THE SAFE OPERATIONAL REQUIREMENTS, WARNINGS AND CAUTIONS. USE THE PRODUCT CORRECTLY AND WITH CARE FOR THE PURPOSE FOR WHICH IT IS INTENDED. FAILURE TO DO SO MAY CAUSE DAMAGE AND/OR PERSONAL INJURY AND WILL INVALIDATE THE WARRANTY. PLEASE KEEP INSTRUCTIONS SAFE FOR FUTURE USE.

1. THE MAIN STRUCTURE PARAMETERS

Power Supply: 100-130Volt~50Hz	Safety Rating: IP44
LED Consumption: 30Watt	Lamp Head size: 130x95x650mm
Number of LED: 140 LED SMD2835	Light angle: 120°
Color Temperature: 6400K	Ambient: -25°C ~ +60°C
Lumen: 2600LM	Cable: H05VV-F 3x1.5mm x 6M totally
Class: I	

Plug & Coupler
Fitted with 110V 16A plug
Fitted with 110V 16A coupler
16 amp current (Max 1500W)
Maximum link 25 lights
Maximum total load applied to the
Coupler should not exceed 1500W



2. SPECIFICATION

To be read full before installation and keep for future reference Safety instruction

- User should check the lamp body and lens carefully before use it.
- Always check that the voltage displayed on the nameplate is the same as the mains power source.
- Never use an electrical appliance in the rain, in wet areas or with wet hands, using electrical appliance under these conditions greatly increases the possibility of electric shock.
- Prior to operation, carefully inspect the light for any damage. Any part that is damaged, including the casing, cable or plug, should be properly and safely repaired or replaced by a qualified electrician before the light is used.
- Please ensure that you read these instructions before using the LED Light, and that all the safety guidelines are understood. Please keep these instructions for future reference.
- Ensure the cable is positioned to avoid presenting a trip hazard.
- Do not exceed the rated power loading for each type of lamp.
- This is of Class I construction and must be earthed.

3. PRODUCT SPECIFICATIONS

- Water Proof Fixture • cable • Fitted with 110V 16A plug & coupler

4. PRODUCT SPECIFICATIONS

- Housing material: Polycarbonate body, and opal glary free PC diffuser.
- LED & Drive: Used for SMD2835 30W Aluminum profiles, Replace the LED please consult your local dealer for replacement; Rated life of 30000 hours.
- Wired with 3m 1.5mm PVC yellow cable and fitting with 110V 16A plug (BS EN 60309).
- Wired with 3m 1.5mm PVC yellow cable and fitting with 110V 16A coupler (BS EN 60309).
- The LED Light also features a power outlet the can be used to link several lamps together or as convenient power source for use with a power tool. Please note the total load applied should not exceed the following:
Maximum power outlet load 1500W.

5. SAFETY WARNING

- This unit must only be connected to an appropriate power supply.
- When not in use always disconnect from the power supply.
- Never leave the unit in use without supervision.
- Do Not use if the unit or the power cord appears to be damaged.
- Ensure the mains cable does not present a trip hazard.
- Do not run cable across walkways. Once the cable has been routed secure cable in position.
- Ensure the mains power cable is fully unwound before use.
- Do not remove plug from mains supply by pulling on power card.
- If the external flexible cable or cord of the cable is damaged, it shall be exclusive replaced by the manufacturer or his service agent or a similar qualified person in order to avoid a hazard.
- In some States, Territories or Work Sites, Operator training or equipment documentation documentation may be required.
- Please check with your Local Regulatory Authority prior to use.
- The unit must only be connected to a reduced low voltage power supply.
The unit is suitable for temporary lighting application.

NOTE

This marking indicates that this product should not be disposed with other household wastes throughout the EU. To prevent possible harm to the environment or human health from uncontrolled waste disposal, recycle it responsibly to promote the sustainable reuse of material resources. To return your used device, please use the return and collection systems or contact the retailer where the product was purchased. They can take this product for environmental safe recycling.